

DINGLI

LEO 23GT

SPIDER LIFT-CRAWLER

DINGLI[®]
Exceed · New Height

LEO 23GT

PERFORMANCE

Working height, max.	23.00 m
Platform height, max.	21.00 m
Horizontal outreach, max. (200 kg)	11.20 m
Up and over clearance, max.	11.50 m
Platform capacity, max.	200 kg
Jib, movable	-
Platform, rotatable	180 °
Turntable rotation, max.	360 °
To be jacked up on ground slope of	16.7 ° / 30.0 %
Track drive, height- and width-adjustable	23 / 45 cm
Gradeability, max.	16.7 ° / 30.0 %
Slope angle, max.	15.5 ° / 27.0 %
Travel speed, max.	1.3 km/h

MEASUREMENTS*

Platform (height) (A)	1.10 m
Platform (length) (B)	1.40 m
Platform (width) (C)	0.70 m
Length (D)	6.20 m
Length without platform (E)	-
Height (F)	1.97 m
Width, min. (G)	0.98 m
Ground clearance, max. (H)	0.40 m
Track (length x width) (I)	1.45 x 0.20 m
Outrigger footprint both side wide (length) (J)	4.53 m
Outrigger footprint both side wide (width) (K)	4.33 m
Outrigger footprint one side narrow (length) (L)	5.98 m
Outrigger footprint one side narrow (width) (M)	3.42 m
Outrigger footprint both sides narrow (width) (N)	2.58 m
Outrigger plate Ø	0.18 m

WEIGHT*

Total weight	2990 kg
Live load in travelling position	4.02 kN/m ²
Live load in working position	1.78 kN/m ²
Point load per outrigger plate, max.	22.40 kN

POWER SOURCES

Standard power sources:	
Electric motor	(country-specific 1-phase)
Combustion engine (Diesel)	Kubota Z602 (10.8 kW / 14.5 hp)
Optional power source:	
Battery drive (AGM)	48 V
Fuel tank capacity (Diesel engine)	12.0 l

POWER SUPPLY

Electric current, max.	country-specific, on request
------------------------	------------------------------

STANDARDS

Harmonised standard DIN EN 280:2016

