

# DINGLI

# VERTICAL LIFTS

## PUSH AROUND - SINGLE MAST



### Standard Equipment

- Tilt Back Frame(Only For GTWY12.5/14-1300)
- Swing Outriggers With Interlock
- Emergency Stop Button
- Emergency Lowering System
- Easy Loading In Pickup Trucks
- Two Controllers Operation
- Leveling Sensor
- Forklift Pockets
- Transport Tie Hole
- Deadman Switch
- All Motion Alarm
- Cylinder Holding Valve
- Flashing Beacon
- Onboard Diagnostic System

### Options

- AC Power to Platform
- Overload Sensor With Alarm



# DINGLI

## VERTICAL LIFTS

### PUSH AROUND - SINGLE MAST



Model	GTWY9.5-1300	GTWY11-1300	GTWY12.5-1300	GTWY14-1300
S.W.L	150kg	150kg	150kg	136kg
Max. Occupants	1	1	1	1
Max. Working Height <b>A</b>	9.50m	11.00m	12.50m	14.00m
Max. Platform Height <b>B</b>	7.50m	9.00m	10.50m	12.00m
Overall Length (Stowed) <b>C</b>	1.30m	1.34m	1.53m	1.53m
Overall Length (Tilted Back) <b>D</b>	/	/	2.63m	3.04m
Overall Width <b>E</b>	0.75m	0.75m	0.75m	0.75m
Overall Height (Stowed) <b>F</b>	1.99m	1.99m	2.35m	2.77m
Overall Height (Tilted Back) <b>G</b>	/	/	1.70m	1.95m
Outrigger Footprint <b>H</b> / <b>I</b>	1.70/1.86m	1.70/1.86m	2.08/2.15m	2.08/2.15m
Platform Size (Length/Width)	0.70x0.60m	0.70x0.60m	0.70x0.60m	0.70x0.60m
Ground Clearance	0.055m	0.055m	0.055m	0.055m
Lifting Motor - AC	220VAC/1.5kW	220VAC/1.5kW	220VAC/1.5kW	220VAC/1.5kW
Lifting Motor - DC	12VDC/1.5kW	12VDC/1.5kW	12VDC/1.5kW	12VDC/1.5kW
Up/Down Speed	28/18sec	34/22sec	40/26sec	45/29sec
Batteries	12V/85Ah	12V/85Ah	12V/85Ah	12V/85Ah
Integrated Charger	12V/15A	12V/15A	12V/15A	12V/15A
Tyres (Front Wheels)	8in	8in	8in	8in
Tyres (Back Wheels)	5in	5in	5in	5in
Weight - AC	430kg	450kg	530kg	559kg
Weight - DC	453kg	472kg	553kg	588kg

